

Processing Equipment

1997 TOSHIBA

610 Ton / 104.0 oz.

Machine Specifications

- Min. Mold Height: 15.50"
- Max. Mold Height: 68.00"
- Max. Daylight: 47.00"
- Tie Bar Spacing: 33.80" x 33.80"
- Core Pull and Valve Gate

1998 TOYO

500 Ton / 55.0 oz.

Machine Specifications

- Min. Mold Height: 13.78
- Max. Mold Height: 36.22"
- Max. Daylight: 46.70"
- Tie Bar Spacing: 34.25" x 34.25"
- Core Pull and Valve Gate

1988 TOSHIBA

500 Ton / 62.8 oz.

Machine Specifications

- Min. Mold Height: 15.80"
- Max. Daylight: 55.00"
- Tie Bar Spacing: 31.80" x 31.80"
- Core Pull and Valve Gate

1998 TOYO

500 Ton / 67.9 oz.

Machine Specifications

- Min. Mold Height: 13.78"
- Max. Mold Height: 36.22"
- Max. Daylight: 46.70"
- Tie Bar Spacing: 34.25" x 34.25"
- Core Pull and Valve Gate

1993 Kawaguchi

450 Ton / 61.0 oz.

Machine Specifications

- Min. Mold Height: 15.50"
- Max. Mold Height: 29.53"
- Max. Daylight: 51.00"
- Tie Bar Spacing: 32.28" x 32.28"
- Core Pull and Valve Gate

2003 TOYO

400 Ton / 45.3 oz.

ALL ELECTRIC PRESS

Machine Specifications

- Min. Mold Height: 11.81"
- Max. Mold Height: 30.31"
- Max. Daylight: 25.60"
- Tie Bar Spacing: 31.89" x 31.89"
- Core Pull and Valve Gate

1998 TOYO
400 Ton / 45.3 oz.

Machine Specifications

- Min. Mold Height: 11.81"
- Max. Mold Height: 29.52"
- Max. Daylight: 27.60"
- Tie Bar Spacing: 31.89" x 31.89"
- Core Pull and Valve Gate

1993 TOSHIBA
390 Ton / 62.8 oz.

Machine Specifications

- Min. Mold Height: 10.00"
- Max. Daylight: 49.20"
- Tie Bar Spacing: 27.90" x 27.90"
- Core Pull and Valve Gate

2001 TOSHIBA
390 Ton / 62.8 oz.

Machine Specifications

- Min. Mold Height: 11.80"
- Max. Daylight: 49.20"
- Tie Bar Spacing: 28.70" x 28.70"
- Core Pull and Valve Gate

2001 TOSHIBA
390 Ton / 63.0 oz.

Machine Specifications

- Min. Mold Height: 11.80"
- Max. Daylight: 49.20"
- Tie Bar Spacing: 28.70" x 28.70"
- Core Pull and Valve Gate

2001 TOSHIBA
310 Ton / 40.9 oz.

Machine Specifications

- Min. Mold Height: 11.80"
- Max. Daylight: 41.70"
- Tie Bar Spacing: 24.00" x 25.25"
- Core Pull and Valve Gate

1998 TOSHIBA
310 Ton / 30.2 oz.

Machine Specifications

- Min. Mold Height: 11.80"
- Max. Daylight: 41.70"
- Tie Bar Spacing: 24.00" x 25.25"
- Core Pull and Valve Gate

1996 TOYO
300 Ton / 32.8 oz.

Machine Specifications

- Min. Mold Height: 13.70"
- Max. Mold Height: 21.60"
- Max. Daylight: 51.00"
- Tie Bar Spacing: 24.00" x 24.00"
- Core Pull and Valve Gate

1998 TOYO
300 Ton / 32.8 oz.

Machine Specifications

- Min. Mold Height: 9.84"
- Max. Mold Height: 25.50"
- Max. Daylight: 51.00"
- Tie Bar Spacing: 28.70" x 28.70"
- Core Pull and Valve Gate

1998 TOYO
300 Ton / 32.8 oz.

Machine Specifications

- Min. Mold Height: 9.84"
- Max. Mold Height: 25.50"
- Max. Daylight: 51.00"
- Tie Bar Spacing: 28.70" x 28.70"
- Core Pull and Valve Gate

1996 KAWAGUCHI
280 Ton / 24.0 oz.

Machine Specifications

- Min. Mold Height: 11.80"
- Max. Mold Height: 21.60"
- Max. Daylight: 41.30"
- Tie Bar Spacing: 24.00" x 24.00"
- Core Pull and Valve Gate

1999 TOYO
245 Ton / 20.8 oz.

Machine Specifications

- Min. Mold Height: 9.84"
- Max. Mold Height: 25.59"
- Max. Daylight: 45.90"
- Tie Bar Spacing: 24.02" x 24.02"
- Core Pull and Valve Gate

1997 KAWAGUCHI
220 Ton / 16.0 oz.

Machine Specifications

- Min. Mold Height: 10.00"
- Max. Mold Height: 21.60"
- Max. Daylight: 41.30"
- Tie Bar Spacing: 22.00" x 22.00"
- Core Pull and Valve Gate

1992 KAWAGUCHI
220 Ton / 19.0 oz.

Machine Specifications

- Min. Mold Height: 9.80"
- Max. Mold Height: 21.70"
- Max. Daylight: 16.70"
- Tie Bar Spacing: 22.00" x 22.00"
- Core Pull and Valve Gate

1992 TOYO
200 Ton / 15.9 oz.

Machine Specifications

- Min. Mold Height: 7.87"
- Max. Mold Height: 19.70"
- Max. Daylight: 37.40"
- Tie Bar Spacing: 20.80" x 20.80"
- Core Pull and Valve Gate

1997 TOSHIBA
190 Ton / 16.0 oz.

Machine Specifications

- Min. Mold Height: 9.10"
- Max. Daylight: 37.40"
- Tie Bar Spacing: 22.00" x 20.00"
- Core Pull and Valve Gate

1995 KAWAGUCHI
180 Ton / 10.0 oz.

Machine Specifications

- Min. Mold Height: 9.80"
- Max. Mold Height: 17.70"
- Max. Daylight: 33.4"
- Tie Bar Spacing: 17.70" x 17.70"
- Core Pull and Valve Gate

1998 TOYO
150 Ton / 6.7 oz.

Machine Specifications

- Min. Mold Height: 5.91"
- Max. Mold Height: 17.72"
- Max. Daylight: 15.8"
- Tie Bar Spacing: 18.10" x 18.10"
- Core Pull and Valve Gate

2000 ENGLE
150 Ton / 10.7 oz.

Machine Specifications

- Min. Mold Height: 7.84"
- Max. Mold Height: 20.47"
- Max. Daylight: 37.0"
- Tie Bar Spacing: Tie Barless
- Core Pull and Valve Gate

1998 TOYO
150 Ton / 6.7 oz.

Machine Specifications

- Min. Mold Height: 5.91"
- Max. Mold Height: 17.72"
- Max. Daylight: 15.8"
- Tie Bar Spacing: 18.10" x 18.10"
- Core Pull and Valve Gate

1997 ENGLE
150 Ton / 11.20 oz.
VERTICAL PRESS

Machine Specifications

- Min. Mold Height: 15.74"
- Max. Mold Height: N/A
- Max. Daylight: 31.49"
- Core Pull and Valve Gate

1992 KAWAGUCHI
100 Ton / 4.6 oz.

Machine Specifications

- Min. Mold Height: 7.09"
- Max. Mold Height: 15.75"
- Max. Daylight: 12.9"
- Tie Bar Spacing: 16.40" x 16.40"
- Core Pull and Valve Gate

2000 ENGLE
100 Ton / 8.3 oz.

Machine Specifications

- Min. Mold Height: 9.84"
- Max. Mold Height: 15.70"
- Max. Daylight: 32.0"
- Tie Bar Spacing: Tie Barless
- Core Pull and Valve Gate

1999 TOSHIBA
90 Ton / 3.8 oz.

Machine Specifications

- Min. Mold Height: 6.70"
- Max. Mold Height: N/A
- Max. Daylight: 24.8"
- Tie Bar Spacing: 14.25" x 14.50"
- Core Pull and Valve Gate

1996 TOYO
55 Ton / 2.7 oz.

Machine Specifications

- Min. Mold Height: 4.72"
- Max. Mold Height: 9.84"
- Max. Daylight: 27.5"
- Tie Bar Spacing: 12.75" x 11.75"
- Core Pull and Valve Gate

1997 ARBURG
40 Ton / 2.0 oz.

Machine Specifications

- Min. Mold Height: 5.30"
- Max. Mold Height: 12.20"
- Max. Daylight: 17.3"
- Tie Bar Spacing: 8.60"